

INDUSTRY REFERENCES

- A. ASTM C 39 - Standard Test Method for Compressive Strength of Cylindrical Concrete Specimens.
- B. ASTM C 177 - Standard Test Method for Steady-State Heat Flux Measurements and Thermal Transmission Properties by Means of the Guarded-Hot-Plate Apparatus.
- C. ASTM C 192 - Standard Practice for Making and Curing Concrete Test Specimens in the Laboratory.
- D. ASTM C 482 - Standard Test Method for Bond Strength of Ceramic Tile to Portland Cement.
- E. ASTM C 1670 - Standard Manufacturer Specification for Adhered Manufactured Stone Masonry Veneer Units.
- E. ASTM C 1780 - Installation Guide & Detailing Options for Adhered Manufactured Stone Veneer.
Visit <https://ncma.org/resource/msv-installation-guide/> for official ASTM C1780 Compliant Installation Guide.
- G. UL 723 - Standard for Safety for Surface Burning Characteristics for Building Materials.

WARNING: Concrete veneer contains Crystalline Silica (quartz) and traces of other hazardous substances which are released as dust and can be inhaled when dry-cutting, drilling, or shaping the product. Crystalline Silica is a chemical known to the State of California to cause cancer, birth defects, and other reproductive harm. Use appropriate safety precautions.